

23rd November, 2016

Technical information for the wheel:

4J x 13 H2-4-30

| | |
|-----------------------|--|
| Wheel Part No. | : SSWL427 |
| Wheel Size | : 4J x 13 H2 ET30 |
| Application | : Car Trailer |
| Center Hole | : $\varnothing 57^{+0.5}$ mm |
| Pitch Circle Diameter | : $\varnothing 100$ mm |
| No. of stud Holes | : 4 |
| Stud Hole Size | : B12EC60 |
| Wheel Centering | : Bolt Centering |
| Inset | : 30 mm |
| Valve Recommendation | : ETRTO- V2.03.1, V2.03.2 |
| Load Capacity | : 500 Kg / LI 84 at 140 km/h |
| Wheel Weight | : 6 Kg |
| Wheel Fastener | : Wheel Screw- M12x1.5 with 60° Conical Head |
| Torque Recommendation | : 120 N-m |
| Hub flange diameter | : Min. $\varnothing 139$ mm |

We recommend circular hub to avoid negative behavior on wheel endurance.

For Steel Strips Wheels Limited

Authorised Signatory

Works & Regd. Office : Vill. Somalheri/Lehi, P.O. Dappar, Tehsil Derabassi, Distt. Mohali, Punjab (India)

Tel. : +91 (1762) 275249, 275872, 275173 Fax : +91 (1762) 275228

Email : admin@sswlindia.com Website : www.sswlindia.com

Delhi Office

: S-2, Second Floor, Vasant Square Mall, Community Center, Pocket V, Plot No. A, Sector B, Vasant Kunj, New Delhi - 110 070, Phone-011-40000378, 377, 376

